

STRAIGHT HANDLE MANUAL GOUGING TORCHES

FEATURES & BENEFITS

RELIABLE TORCH DESIGN

- Market leader for over 60+ years
- Greater operator comfort

ACCEPTS A WIDE RANGE OF CCDC GOUGING ELECTRODES

- 5/16" (7.9 mm) - through 5/8" (15.9 mm) round

DURABLE FRONT INSULATORS

- High impact and heat resistant protecting the torch metal parts

SWIVEL CABLE

- Less cable twist
- Less strain on the operator

HIGH QUALITY CABLE HOSE

- Best quality cable hose offers high heat and abrasion resistance
- Non-conductive

RUGGED CONSTRUCTION OVERALL

- Can withstand harsh environments

K-5

Extra Heavy Duty - Heavy metal removal applications such as weld preparations in pressure vessel shops, shipyards and defect removal in foundries



AMPERAGE RANGE

- 450 - 1250 amps

ELECTRODE SIZE

- Pointed - 5/16" - 1/2" round (7.9 mm - 12.7 mm)
- Jointed - 5/16" - 5/8" round (7.9 mm - 15.9 mm)
- Half Round - 5/8" (15.9 mm)

AIR REQUIREMENTS

- psi - 80
- kg/cm² - 5.6
- cfm - 30
- l/min - 850

| Part No. | Description |
|------------|--|
| 01-104-003 | Torch Only |
| 61-104-007 | Torch w/7 ft (2.1 m) 360° Swivel Cable |
| 61-104-008 | Torch w/10 ft (3 m) 360° Swivel Cable |

CUTSKILL MANUAL GOUGING TORCHES

FEATURES & BENEFITS

NATURAL 15° TORCH ANGLE

- Greater operator comfort

DURABLE FRONT INSULATORS

- High impact and heat resistant protecting the torch metal parts

360° SWIVEL CABLE

- Less cable twist
- Less strain on operator

POSITIVE GRIP HANDLE

- Greater operator feel and ease in positioning the torch

REDUCED WEIGHT

- Optimum cable and torch weight to minimize fatigue

HIGH QUALITY CABLE HOSE

- Best quality cable hose offers high heat and abrasion resistance
- Non conductive

CSK4000

Heavy Duty - Heavy metal removal applications such as weld preparations in pressure vessel shops and shipyards



ELECTRODE SIZE

- Pointed - 5/32" - 1/2" round (4.0 mm - 12.7 mm)
- Jointed - 5/16" - 1/2" round (7.9 mm - 12.7 mm)
- Flat - 3/8" and 5/8" (9.5 mm - 15.9 mm)
- Half Round - 5/8" (15.9 mm)

AIR REQUIREMENTS

- Maximum Amperage - 1000 amps
- Compressed Air - 80 psi (5.6 kg/cm²)
- Compressed Air Flow Rate - 28 cfm (0.79 m³/min)
- Torch and Cable Weight: 5.4 lbs (2.4 kg)

| Part No. | Description |
|------------|-------------------------------------|
| 01-088-000 | Torch Only |
| 61-088-007 | Torch & 7 ft (2.1 m) Cable Assembly |
| 61-088-010 | Torch & 10 ft (3 m) Cable Assembly |
| 70-088-007 | 7 ft (2.1 m) Cable Assembly |
| 70-088-010 | 10 ft (3 m) Cable Assembly |