



6 m/19,7' - 7,6 m/25'  
15,2m/50'

0,4 Kg / 0,88 lb  
1 m  
3,3'

**NO HF**

V peak 500 5 bar

X 60%	X 100%		
40 A	30 A	110 l/min	15 mm 3/5"
60 A	45 A	120 l/min	25 mm 1"
80 A	65 A	140 l/min	32 mm 1 1/4"
110 A	85 A	155 l/min	40 mm 1 3/5"
130 A	105 A	180 l/min	45 mm 1 3/4"



CODE	↔	
PAZ006D-004-FA3	6 m / 19,7'	Central Adaptor
PAZ008D-004-FA3	7,6 m / 25'	Central Adaptor
PAZ015D-004-FA3	15,2 m / 50'	Central Adaptor
PAZ006D-000-FA3	6 m / 19,7'	1/4 G
PAZ008D-000-FA3	7,6 m / 25'	1/4 G
PAZ015D-000-FA3	15,2 m / 50'	1/4 G
PAZ006D-304-FA3	6 m / 19,7'	Trafimector®
PAZ008D-304-FA3	7,6 m / 25'	Trafimector®
PAZ015D-304-FA3	15,2 m / 50'	Trafimector®

CODE	↔	
PAZ006D-100-FA3	6 m / 19,7'	Hypertherm® PWM 1000 - 1250 - 1650
PAZ008D-100-FA3	7,6 m / 25'	Hypertherm® PWM 1000 - 1250 - 1650
PAZ015D-100-FA3	15,2 m / 50'	Hypertherm® PWM 1000 - 1250 - 1650
PAZ006D-200-FA3	6 m / 19,7'	Lincoln Tomahawk® 1538
PAZ008D-200-FA3	7,6 m / 25'	Lincoln Tomahawk® 1538
PAZ015D-200-FA3	15,2 m / 50'	Lincoln Tomahawk® 1538



Starter kit  
NOT INCLUDED  
(see page 13)



ONLY FOR DEALER

CODE	↔		+	CODE	KIT
PAZ006D-000-FA3	6 m / 19,7'	1/4 G		PT0500	Miller Spectrum® 2050 - 650 - 701
PAZ008D-000-FA3	7,6 m / 25'	1/4 G		PT0501	Hypertherm® PWM 1000 - 1250 - 1650
PAZ015D-000-FA3	15,2 m / 50'	1/4 G		PT0502	Lincoln Tomahawk® 1538
				PT0503	Hypertherm® 600 - 800

