

TIG WELDING



TIG 26 US



V peak	113	Argon	0.5 ± 4.0 0.020" ± 5/32"
X	180A DC 35% 150A AC		

CODE	↔				REF
SK4427-35	4 m / 12,5'	2 cables			26-12-2
SK4448-35	4 m / 12,5'	1 cable			26-12-R
SK4827-35	8 m / 25'	2 cables			26-25-2
SK4848-35	8 m / 25'	1 cable			26-25-R
SL4427-35	4 m / 12,5'	2 cables flex			26F-12-2
SL4448-35	4 m / 12,5'	1 cable flex			26F-12-R
SL4827-35	8 m / 25'	2 cables flex			26F-25-2
SL4848-35	8 m / 25'	1 cable flex			26F-25-R
SM4427-35	4 m / 12,5'	2 cables valve			26V-12-2
SM4448-35	4 m / 12,5'	1 cable valve			26V-12-R
SM4827-35	8 m / 25'	2 cables valve			26V-25-2
SM4848-35	8 m / 25'	1 cable valve			26V-25-R
SO4427-35	4 m / 12,5'	2 cables flex - valve			26FV-12-2
SO4448-35	4 m / 12,5'	1 cable flex - valve			26FV-12-R
SO4827-35	8 m / 25'	2 cables flex - valve			26FV-25-2
SO4848-35	8 m / 25'	1 cable flex - valve			26FV-25-R



only for extra EU markets

All trademarks are of exclusive property of the respective companies | Data and images are indicative and may be changed in any time without notice | Copyright © 2012 Trafimet Spa

