

MIG/MAG WELDING

TMAX 400

trafimet
distribution

trafimet
welding & cutting

TMAX
EVOLUTION OF THE SPECIES



3 - 4,6 m
10' - 15'

1,3 Kg
2,87 lb

1 m
3,3'

V
peak

113

mm

1,0 - 1,6 mm
.040" - 1/16"

X
60%

450A CO₂
400A Mix


CODE	↔	Ⓜ
MA6385	3 m / 10'	EURO - TW
MA6386	4 m / 12'	EURO - TW
MA6387	4,6 m / 15'	EURO - TW
MA6394T	3 m / 10'	TWECO®
MA6395T	4 m / 12'	TWECO®
MA6396T	4,6 m / 15'	TWECO®
MA6394M	3 m / 10'	MILLER®
MA6395M	4 m / 12'	MILLER®
MA6396M	4,6 m / 15'	MILLER®
MA6394L	3 m / 10'	LINCOLN®
MA6395L	4 m / 12'	LINCOLN®
MA6396L	4,6 m / 15'	LINCOLN®



CODE	↔	Ⓜ	+	CODE	KIT
MA6394	3 m / 10'	5/8-18 UNF		AR0170	Tweco® 1/4 KIT
MA6395	4 m / 12'	5/8-18 UNF		AR0172	Lincoln® KIT
MA6396	4,6 m / 15'	5/8-18 UNF		AR0173	Miller® KIT

Liner included

Kit to be assembled by a qualified technician



ME0367
brass

51
M9x1

Ø mm	Ø in	Cu for Al	CuCrZr
0,8	.030		MD0250-78
0,9	.035		MD0250-79
1,0	.040		MD0250-80
1,2	.045	MD0250-62	MD0250-82
1,4	.052	MD0250-64	MD0250-84
1,6	1/16	MD0250-66	MD0250-86
2,0	5/64		MD0250-90
2,4	3/32		MD0250-94

38
M9x1
Ø 10

MC0298	MC0011	MC0012	MC0013
82 Ø 14	82 Ø 16 5/8"	82 Ø 18	82 Ø 20

STANDARD (REF)

MT0260
BX0742
MQ0340
MF0367
FB0653
50 mm²
MH0473. 3 m / 10'
MH0474. 4 m / 12'
MH0475. 4,6 m / 15'EA0374
MT0077
EA0014
BW0327
EA0064
BW0265
MH0473. 3 m / 10'
MH0474. 4 m / 12'
MH0475. 4,6 m / 15'EA0342
BW0254
EA0083
Euro TW
FA0027
MQ0129
BW0480
FB0395
pre-drilled for radial gas
5/8-18 UNF

Wire	grey color
1,2 + 1,6 .045" + 1/16"	Steel
5 m 16,4'	GM0013 (44-116-15)