

MIG/MAG WELDING

TMAX 500

trafimet
distribution

trafimet
welding & cutting

TMAX
EVOLUTION OF THE SPECIES



3 - 4,6 m
10' - 15'

1,4 Kg
3,2 lb

1 m
3,3'

V
peak

113

Ø
mm


1,0 - 2,0 mm
.040" - 5/64"

X
60%


550A CO₂
500A Mix

CODE	↔	Ⓜ
MA6485	3 m / 10'	EURO - TW
MA6486	4 m / 12'	EURO - TW
MA6487	4,6 m / 15'	EURO - TW
MA6494T	3 m / 10'	TWECO®
MA6495T	4 m / 12'	TWECO®
MA6496T	4,6 m / 15'	TWECO®
MA6494M	3 m / 10'	MILLER®
MA6495M	4 m / 12'	MILLER®
MA6496M	4,6 m / 15'	MILLER®
MA6494L	3 m / 10'	LINCOLN®
MA6495L	4 m / 12'	LINCOLN®
MA6496L	4,6 m / 15'	LINCOLN®

CODE	↔	Ⓜ	+	CODE	KIT
MA6494	3 m / 10'	5/8-18 UNF		AR0170	Tweco® 1/4 KIT
MA6495	4 m / 12'	5/8-18 UNF		AR0172	Lincoln® KIT
MA6496	4,6 m / 15'	5/8-18 UNF		AR0173	Miller® KIT
Liner included				Kit to be assembled by a qualified technician	








ME0368
Copper



51
M9x1

Ø mm	Ø in	Cu for Al	CuCrZr
0,8	.030		MD0250-78
0,9	.035		MD0250-79
1,0	.040		MD0250-80
1,2	.045	MD0250-62	MD0250-82
1,4	.052		MD0250-84
1,6	1/16	MD0250-66	MD0250-86
2,0	5/64		MD0250-90
2,4	3/32		MD0250-94



MC0298	MC0011	MC0012	MC0013
			
82 Ø 14	82 Ø 16 1/2"	82 Ø 18	82 Ø 20

STANDARD (REF)

